

DOUBLE FLANGED PIPE series FF



TECHNICAL CHARACTERISTICS

Flange end connections according to EN1092-2
 Designed according to EN545
 Maximum working pressure: PN16 / 16 bar
 Working temperature: 0°C - +70°C
 Color RAL5015
 Powder epoxy coating 250 µm thickness
 Drilling of flanges: PN10/16, starting from DN200 - PN10
 Body from ductile iron EN-GJS-500-7
 WRAS approved epoxy coating,
 ACS approved epoxy coating under request

DN	Flange drilling	L	e	Weight	BLUCAST ref. no.	DN	Flange drilling	L	e	Weight	BLUCAST ref. no.
50	PN10/16	100	7	4.8	FF050100	150	PN10/16	200	7.8	14.5	FF150200
50	PN10/16	200	7	6.5	FF050200	150	PN10/16	300	7.8	16.2	FF150300
50	PN10/16	300	7	9	FF050300	150	PN10/16	400	7.8	22.4	FF150400
50	PN10/16	400	7	10	FF050400	150	PN10/16	500	7.8	24	FF150500
50	PN10/16	500	7	11	FF050500	150	PN10/16	1000	7.8	46.5	FF1501000
50	PN10/16	1000	7	15	FF0501000	200	PN10	100	8.4	18.9	FF200100
80	PN10/16	100	7	6.4	FF080100	200	PN10	200	8.4	23	FF200200
80	PN10/16	200	7	7.1	FF080200	200	PN10	300	8.4	28.5	FF200300
80	PN10/16	300	7	7.9	FF080300	200	PN10	400	8.4	32	FF200400
80	PN10/16	400	7	9	FF080400	200	PN10	500	8.4	37	FF200500
80	PN10/16	500	7	12.1	FF080500	200	PN10	1000	8.4	60	FF2001000
80	PN10/16	1000	7	22.9	FF0801000	250	PN10	1000	9	78	FF2501000
100	PN10/16	100	7.2	8	FF100100	300	PN10	100	9.6	41.6	FF300100
100	PN10/16	200	7.2	8.5	FF100200	300	PN10	200	9.6	44.6	FF300200
100	PN10/16	300	7.2	9.9	FF100300	300	PN10	300	9.6	49.5	FF300300
100	PN10/16	400	7.2	11	FF100400	300	PN10	400	9.6	60	FF300400
100	PN10/16	500	7.2	12.8	FF100500	300	PN10	500	9.6	71.8	FF300500
100	PN10/16	1000	7.2	24.5	FF1001000	300	PN10	1000	9.6	130	FF3001000
150	PN10/16	100	7.8	13	FF150100						

